



产品编号: WCD0000150
日期: 2018/01/24
版本号: V1.0

>>> 产品参数 Specification <<<

Page

1/2

UHF(9662) WHITE PVC CARD

尺寸 Card Size

85.5X54mm

天线尺寸/材质 Antenna Size / Material

70X17mm

PVC

厚度 Thickness

0.76-0.84mm

芯片 Chip

H3(9662)

频段/协议 Resonance Frequency / Protocol

860-960 Mhz

IEC18000-6C EPC Class1 Gen2

内存

Memory

EPC: 96 bits

TID: 64 bits

USER: 512 bits

芯片使用寿命 IC Life

10万次擦写, 数据保存10年

100,000 Programming cycles, 10years data retention


读距/读卡器 Reading Distance / Reference Reader

4 – 5 cm


RS-1300



实物图 (Product Image)



天线 (Antenna)



结构图 (Structure)

用途 Application

企业一卡通、公交卡、高速公路收费卡、停车场、
小区管理系统、会员积分、水表预付费、酒店房卡等。
Business card/Bus Card/Freeway toll card/
Parking lot card/Community Management System/
Vip card/Hotel room card etc.



产品编号: WCD0000150
日期: 2018/01/24
版本号: V1.0

>>> 产品参数 Specification <<<

Page

2/2

特殊工艺 Features (Option)

流水号打码 / UID打码 / 二维码 / 加密 / 磁条 等
Serial NO. / UID / Barcode / Encoding / Mag strip , etc.

包装 Packing



数量 / 箱
Qty / Box
200 pcs

数量 / 箱
Qty / Carton
1000 pcs
2000 pcs
3000 pcs

箱子尺寸
Carton Dimension
31X22X12 cm
32X23.5X21 cm
23X19X51 cm

操作/储存温度 Temperature / Humidity

操作温度(Operating Temperature/Humidity): [-15°C to +65°C] 20% to 90% RH Non-condensing;
适用温度(Storage Temperature/Humidity): [-25°C to +50°C] 20% to 90% RH Non-condensing;

保质期 Shelf Life

使用密封包装、在+23°C±5°C / 50%±10%RH条件下1年。
From the date of manufacture, 1 year in vacuumed bag at +23°C±5°C / 50%±10%RH)。

声明: 以上环境要求的建议基于我司最新的知识和现有经验基础上, 本公司保留产品最终解释权。本文件权属我司, 示经我司许可, 不得复制, 转寄等一切侵权活动。

Disclaimer: Our recommendations are based on our latest knowledge and experience, we reserve all rights for final explanation. The information contained on this document is considered to be confidential material proprietary to us, and this information shall not be disclosed, duplicated or copied for any purpose, nor made available for any third party without the prior consent to our company.